

LXF₂-300x1000

铝门窗双头仿形铣床 Double-head Copy-routing Milling Machine

[性能特点]

- 该机可用于铝门窗的内外全仿形的仿形铣削加工。
- 采用仿形模板和辅助定位两种仿形方式。
- 使用脚踏开关控制压紧气缸，安全可靠。

[Product Features]

- This machine can be used for the copy-routing milling of the inner and outer full copy-routing of aluminum windows and doors.
- It uses two copy-routing methods: copy-routing template and auxiliary positioning.
- The clamping is controlled by a foot pedal switch, which is safe and reliable.
- Simple model adjustment and replacement, wide adaptation, high efficiency.

技术参数 Technical Parameters

电源	Power supply	380v 50Hz
转速	Rotation	3000/min
输入功率	Input power	2 × 0.75kW
铣刀直径	Diameter of the milling cutter	φ5、φ8
仿形触头直径	Diameter of copy-routing head	φ5、φ8
仿形范围	Copy-routing Range	300mm
加工面的直线度	Processing deviation from straightness	±0.1 mm
铣削型面粗糙度	Profile surface roughness	Ra12.5
机床外形尺寸	Contour dimension	4050 × 950 × 1500mm(L × W × H)
重量	Weight	250kg

